Public reporting burden fo	r this collection of information i		ION PAGE		OMB No. 0704-0188
					searching existing data sources, gathering and ther aspect of this collection of information,
1 DIUDWAY SING 1204 Arbir	naton VA 22202-4302 Doone	andonia abaddit	The state of the s	ior insormation operatio	113 dilu nebula lu/u4-u iARI 1215 laffarean nauta
1. REPORT DATE	it does not display a currently	valid OMB control number. PLE	otwithstanding any other provision EASE DO NOT RETURN YOUR F	ORM TO THE ABOVE	e subject to any penalty for failing to comply with a NDDRESS.
EFORT DATE	(DD-IVIIVI-TTTT)	2. NEPURI TYPE			3. DATES COVERED (From - To)
4. TITLE AND SUB	TITI F	Technical Papers			
" ITTEL AND GOD	IIILL		,		5a. CONTRACT NUMBER
			•	-	
				J '	5b. GRANT NUMBER
				<u></u>	:
					c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)			· · · · · · · · · · · · · · · · · · ·		
		·		1	od. PROJECT NUMBER
				<u> </u>	2306
				;	e. TASK NUMBER
				<u></u>	M183
					f. WORK UNIT NUMBER
7. PERFORMING O	RGANIZATION NAME	(S) AND ADDRESS(ES	,		· ·
	TOTAL TENED	(3) AND ADDRESS(ES	P)	5	PERFORMING ORGANIZATION
Air Force Researc	h Laboratory (AFM	C)	•		REPORT
AFRL/PRS	, (-,		J	1
5 Pollux Drive	*		•	1	
Edwards AFB CA	93524-7048			1	
				1	1
9. SPONSORING / N	MONITORING AGENC	Y NAME(S) AND ADDE	TCC/EC)		
		T MANIE(S) AND ADDI	(ESS(ES)	1	0. SPONSOR/MONITOR'S
				A	CRONYM(S)
Air Force Researc	h Laboratory (AFM	C)		ł	
AFRL/PRS	•	,		L ₄	1 SDONGOD/HONE
5 Pollux Drive				'	1. SPONSOR/MONITOR'S
Edwards AFB CA	93524-7048				NUMBER(S)
12 DISTRIBUTION	AVAILABILITY STAT				
12. DISTRIBUTION /	AVAILABILITYSTAT	EMENT			
					ļ
Approved for publ	ic release; distributio	on unlimited			. "
rr	io rolouso, distributio	m ummmed.			
13. SUPPLEMENTAL	DV NOTES				
JOH I EEMENTA	II NOTES				
					:
14. ABSTRACT					
					:
					ļ
		•			
					,
					İ
			,		
		¥ 1			
5. SUBJECT TERMS			· · · · · · · · · · · · · · · · · · ·		
C OFOUR TO					1
6. SECURITY CLASS	SIFICATION OF:		17. LIMITATION	18. NUMBER	19a. NAME OF RESPONSIBLE
			OF ABSTRACT	OF PAGES	PERSON
. REPORT	h ARCTRACT	- TIPO - 4			Leilani Richardson
0111	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER
Inclassified	Unclassified	Unclassified	(A)		(include area code)
	- mondonineu	Lonciassified		1	(661) 275-5015

REPORT DOCUMENTATION PAGE

6 separate Hems are enclosed.

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. 239.18

Form Approved

100

6 /

MEMORANDUM FOR PR (Contractor/In-House Publication)

FROM: PROI (TI) (STINFO)

26 Jun 2000

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-AB-2000-142 P. Wapner (ERC); W. Hoffman, "Microsensors that Function on the Basis of Surface and Wettability" (Abstract)

Fall Meeting of Materials Research Society (Boston, MA, 03 Dec 2000)

(Statement A)

(Boston, MA, 03 Dec 2000) (Submission Deadline: 10 Jul 2000)

b.) military/national critical technology, c.) export	and e.) technical sensitivity and/or economic sensitivity.
Signature	
and/or b) possible higher headquarters review. Comments:	ffairs Office for: a.) appropriateness for public release
Signature	Date
e.) parallel review completed if required, and f.) for Comments:	nilitary/national critical technology, d.) economic sensitivity, ormat and completion of meeting clearance form if required
Signature	
appropriateness of distribution statement, d.) technational critical technology, and f.) data rights and	echnical accuracy, b.) appropriateness for audience, c.) nical sensitivity and economic sensitivity, e.) military/ I patentability

APPROVED/APPROVED AS AMENDED/DISAPPROVED

PHILIP A. KESSEL

Date

Technical Advisor

Propulsion Science and Advanced Concepts Division

20021119 091

MICROSENSORS THAT FUNCTION ON THE BASIS OF SURFACE TENSION AND WETTABILITY

profiles that are non-uniform can be used to accurately and reproducibility measure the forces acting upon these droplets. The position of droplets within such micro-sensors is dictated by surface tension, wettability, geometric configuration of the confining walls, and the forces acting upon the droplet. These micro-sensors can measure pressure and acceleration, and can also be made to operate as micro-valves, micro-switches, optical shutters, as well as other devices. They have no moving mechanical parts to wear out, and can theoretically endure high amounts of over-actuation and still return to initial levels of accuracy and precision without harm. The axial profiles of these shaped capillaries are easily fabricated using microtube technology developed at the Air Force Research Laboratory at Edwards Air Force Base. However, it is also possible to use non-circular shaped voids and still achieve similar capabilities with some limitations. These non-circular shaped voids can be manufactured using more conventional MEMS technologies such as photolithography and LIGA.

DISTRIBUTION A. Approved for public release; distribution unlimited.